

# CERTIFICATE

### of constancy of performance 1922 - CPR - 1174

In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product

Resilient, textile and laminate floor coverings. Laminate floor coverings for interior use, thickness: from 7 mm to 12 mm

#### Trade mark FLOORPAN

(with the performance listed, see Annexes I to 1922-CPR-1174 that is an inseparable part of this certificate)

placed on the market under the name or trade mark of

Limited Liability Company «KASTAMONU INTEGRATED WOOD INDUSTRY» 423600, Russian Federation, Tatarstan, Yelabuga, SEZ «Alabuga» territory, SH-3 Street, building 3/3

and produced in the manufacturing plant of

Limited Liability Company «KASTAMONU INTEGRATED WOOD INDUSTRY» 423600, Russian Federation, Tatarstan, Yelabuga, SEZ «Alabuga» territory, SH-3 Street, building 3/3

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standards

#### EN 14041:2004; EN 14041:2004/AC:2006

under system 1 for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the constancy of performance of the construction product.

This certificate was first issued on 26.06.2019 and will remain valid until 26.06.2020 as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body. The certificate is supported through annual surveillance audit and is reissued after each surveillance audit. The validity of the certificate may be confirmed in the CE register at the web address www.dedal-bg.net.











## ANNEX I TO CERTIFICATE OF CONSTANCY OF PERFORMANCE 1922 - CPR - 1174/26.06.2019

#### Performance list, acc. to EN 14041:2004; EN 14041:2004/AC:2006

| No. | Characteristics              | Clause of the standard | Method              | Result             |
|-----|------------------------------|------------------------|---------------------|--------------------|
| 1   | Reaction to fire             | EN 14041/ 4.1          | EN 13501-1          | B <sub>fl</sub> s1 |
| 2   | Content of pentachlorophenol | EN 14041/ 4.2          | CEN/TR 14823        | ≤ 5 ppm            |
| 3   | Emission of formaldehyde     | EN 14041/ 4.3          | EN 717-1            | E 1                |
| 4   | Water-tightness              | EN 14041/ 4.4          | EN 13553            | N/A                |
| 5   | Slipperiness                 | EN 14041/ 4.5.1        | EN 13893            | DS                 |
| 6   | Electric behaviour           | EN 14041/ 4.6          | EN 1815<br>ISO 6356 | NPD .              |
| 7   | Thermal conductivity         | EN 14041/4.7           | EN ISO 10456        | 0.18 W/mK          |

This certificate was first issued on 26.06.2019 and will remain valid until 26.06.2020 as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body. The certificate is supported through annual surveillance audit and is reissued after each surveillance audit. The validity of the certificate may be confirmed in the CE register at the web address www.dedal-bg.net.



Issued: Burgas, 26 June 2019



